



NOTES:

- |                       |  |
|-----------------------|--|
| 1. DISPLAY TYPE:      | STN/BLUE                                       |
| 2. VIEWING DIRECTION: | 6:00   |
| 3. POLARIZER MODE:    | TRANSFLECTIVE/NEGATIVE                         |
| 4. OPERATING TEMP:    | $-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$ |
| 5. STORAGE TEMP:      | $-30^{\circ}\text{C} \sim +80^{\circ}\text{C}$ |
| 6. LOGIC VOLTAGE:     | 5V   |
| 7. DRIVE METHOD:      | 1/16DUTY 1/5BIAS                               |
| 8. DRIVER IC:         | SPLC780/100                                    |
| 9. BACKLIGHT:         | LED(WHITE)                                     |

PIN	1	2	3	4	5	6	7~14	15	16
SYMBOL	VSS	VDD	V0	RS	R/W	E	DB0~DB7	A(+)	K(-)

 深圳市耀宇科技有限公司 SHENZHEN YAO YU TECHNOLOGY CO., LTD							
DRAW NO.	YMSC-C1602GDBSWSN			DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. A	SCALE:1/1				
 TOLERANCE UNLESS: $\pm 0.3$							