



PIN NO.	1	2	3	4	5	6	7	8	9	10
SIGNAL	VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3
PIN NO.	11	12	13	14	15	16				
SIGNAL	DB4	DB5	DB6	DB7	A	K				

- NOTES:
- 1.DISPLAY TYPE: STN/BLUE
 - 2.VIEWING ANGLE: 6:00
 - 3.POLARIZER MODE:TRANSMISSIVE/NEGATIVE
 - 4.OPERATING TEMP: -10°C ~ +60°C
 - 5.STORAGE TEMP: -20°C ~ +70°C
 - 6.LOGIC VOLTAGE: VDD=5.0V
 - 7.LCD DRIVER VOLTAGE: Vop=4.8V
 - 8.DRIVE METHOD: 1/16DUTY 1/5BIAS
 - 9.DRIVE IC: KS0066
 - 10.BACKLIGHT TYPE: WHITE EDGE LED

		深 圳 市 耀 宇 科 技 有 限 公 司 SHENZHEN YAO YU TECHNOLOGY CO., LTD	
DRAW NO. YMSC-C1602C-3DYLYWN UNIT:mm PAGE:1/1 TOLERANCES UNLESS:±0.3	VER: A SCALE:1/1	DRAWN	ME CHECKED EE CHECKED APPROVED
REV.	DESCRIPTION	DATE	

SCALE:5/1