



1	2	3	4	5	6	7
VDD	VDD	V0	RS	R/W	E	DB0
8	9	10	11	12	13	14
DB1	DB2	DB3	DB4	DB5	DB6	DB7

- NOTES:
- 1.DISPLAY TYPE: STN/BLUE/YELLOW-GREEN
 - 2.VIEWING ANGLE: 6:00
 - 3.POLARIZER MODE: TRANSPARENT/NEGATIVE/POSITIVE
 - 4.OPERATING TEMP: -20°C~+70°C
 - 5.STORAGE TEMP: -30°C~+80°C
 - 6.LOGIC VOLTAGE: VDD=5.0V
 - 7.LCD DRIVER VOLTAGE: Vop=4.7V
 - 8.DRIVE METHOD: 1/16DUTY,1/5BIAS
 - 9.DRIVE IC: SPLC780
 - 10.BACKLIGHT TYPE: LED/WHITE/YELLOW-GREEN



深 圳 市 耀 宇 科 技 有 限 公 司
SHENZHEN YAO YU TECHNOLOGY CO., LTD.

DRAW NO.	YM1602H-1	DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER: A	SCALE:1/1		
	TOLERANCES UNLESS: ±0.2				