



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
NAME	VSS	VDD	VO	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

NOTES:

- | | |
|---------------------------|------------------------|
| 1. DISPLAY TYPE: | STN/YELLOW-GREEN |
| 2. VIEWING DIRECTION: | 6:00 |
| 3. POLARIZER MODE: | TRANSFLECTIVE/POSITIVE |
| 4. OPERATING TEMP: | -20°C~+70°C |
| 5. STORAGE TEMP: | -30°C~+80°C |
| 6. LOGIC VOLTAGE: | 5V |
| 7. LCD OPERATION VOLTAGE: | 4.5V |
| 8. DRIVE METHOD: | 1/16DUTY 1/5BIAS |
| 9. BACKLIGHT: | LED(Y/G) |

 深 圳 市 耀 宇 科 技 有 限 公 司 SHENZHEN YAO YU TECHNOLOGY CO.,LTD							
DRAW NO.	YMSC-C1602G-1DYLYSN			DRAWN	ME CHECKED	EE CHECKED	APPROVED
UNIT:mm	PAGE:1/1	VER. A	SCALE:1/1				
 TOLERANCE UNLESS:±0.2							